

# **SU0634** *Waterproof Manual Callpoint*

## **INFORMATION SHEET**

### **DESCRIPTION**

The SU0634 Manual Call Points feature enhanced environmental protection, allowing the unit to be installed in many external environments where water and dirt are likely to be present, making it a true waterproof and outdoor product.

This surface mounting call point has an International Protection Rating of IP67, making it suitable for outdoor applications. The callpoint is operated by simply pressing on the centre of the frangible element until it snaps, which releases a microswitch, signalling an alarm at the c.i.e.

A plastic coated frangible element ensures safe and reliable operation, and does not produce dangerous glass shards.

The SU0634 is supplied with one normally-open and one normally-closed contact. Selecting either configuration is achieved by locating the terminal block on the appropriate connection. Single pole change-over switching can be achieved using two terminal blocks.



### **SPECIFICATIONS**

Maximum Voltage	30Vdc
Switch Rating	2A
Cable Termination	0.5-2.5mm <sup>2</sup>
Circuit Configuration	Single Pole Changeover Contacts
Operating Temperature	-30°C to +70°C
Humidity	0 to 95% non/cond.
Installation	Waterproof
IP Rating	IP67
Dimensions (mm)	93 x 98 x 70 (HWD)
Weight	270g
Part Numbers	
SU0634	Manual Call Point
5 15.001.025	Replacement Glass (Pk 5)
SC070	Test Key

**tyco**  
Safety Products

[www.tycosafetyproducts-anz.com](http://www.tycosafetyproducts-anz.com)

Tyco Safety Products, a division of Tyco Australia Pty Limited A.B.N. 80 008 399 004, reserve the right to alter specifications without notice, in line with Tyco's policy of continuing product improvement.